

European NEtwork for Redistributing Geospatial Information to user Communities - Open Data



OnoM@p: a Spatial Data Infrastructure dedicated to noise monitoring based on volunteers measurements

Perugia, Italy - October 12th 2016.

Lab-STICC CNRS (E. Bocher, G. Petit, S. Palominos) LAE Ifsttar (J. Picaut, **N. Fortin**, G. Guillaume)





Outline

European NEtwork for Redistributing Geospatial Information to user Communities - Open Data

Introduction

OnoM@p: System components and standards

NoiseCapture application

Web Services

OnoM@p: Operating mode

OnoM@p: Data issues

Quality control

Mapping sound indicators






Introduction

European NEtwork for Redistributing Geospatial Information to user Communities - Open Data

Noise societal and environmental issues

European Communities reports about 80 million people are exposed to unacceptable daytime noise levels > 65 dB(A).

Environ Health Perspect; DOI:10.1289/ehp.1307272







Introduction

European NEtwork for Redistributing Geospatial Information to user Communities - Open Data

At european level

The Environmental Noise Directive (END) 2002/49/CE relating to the assessment and management of environmental noise aims at defining a common approach planned to **avoid**, **prevent** or **reduce** the harmful effects, including annoyance, due to the exposure to environmental noise.

Four main axis:

- monitoring environmental noise;
- informing and consulting the population;
- addressing local noise issues;
- developing a long-term european strategy.





Introduction

European NEtwork for Redistributing Geospatial Information to user Communities - Open Data

... in the context of noise monitoring - the drawing up of strategic noise maps for cities of more than 100 000 inhabitants.

In both **urban** and **suburban areas**, methods to contend with noise pollution consist in various actions (*e.g.* road resurfacing, acoustic screens insertion, speed limits reduction, traffic deviation, new public transportation policies setting up, etc.).


The action plans can be evaluated, before their implementations, through **noise propagation simulations**.





Simulation-based noise maps

European NEtwork for Redistributing Geospatial Information to user Communities - Open Data



http://carto.bruitparif.fr, June 2015





Simulation-based noise maps

European NEtwork for Redistributing Geospatial Information to user Communities - Open Data

But...

- modelling of the main urban noise source, mainly the road traffic, requires many information (e.g. traffic flow, light/heavy vehicles proportion and respective speeds, etc.).
- input data are, most of the time, not available over the study area.
- simulations can only take into account mechanical sound sources (e.g transports, ...) and not the sound levels fluctuations (i.e. sound events).
- Noise simulation maps are static and always out of date (outdated traffic volume).
- → It's difficult to analyze the noise impact at different spatio-temporal granularities.





The smartphone sensing opportunity

European NEtwork for Redistributing Geospatial Information to user Communities - Open Data

Multiple sensors:

- position sensors:
 - a GPS,
 - a magnetometer,
 - a gravity field sensor,
 - a proximity sensor,,
- motion sensors:
 - a 3-axis accelerometer,
 - a gyroscope,
- environmental sensors:
 - a camera,
 - a temperature sensor,
 - a lux meter,
 - a barometer,
 - an air humidity sensor;
 - a microphone.






The smartphone sensing opportunity

European NEtwork for Redistributing Geospatial Information to user Communities - Open Data

87% of the world's population owned a mobile phone subscription

Smartphone Users and Penetration Worldwide, 2013-2018

billions, % of mobile phone users and % change



Note: individuals of any age who own at least one smartphone and use the smartphone(s) at least once per month Source: eMarketer. Dec 2014

182903 www.eMarketer.com

http://www.emarketer.com, June 2015





The project 2014 - 2017

European NEtwork for Redistributing Geospatial Information to user Communities - Open Data

The project objectives are to:

- Develop Virtual Hubs (VHs)
 - different scales: regions, member states, Europe
 - a unique point of access to heterogeneous data sources for end-users and machines.
- Demonstrate the validity of VHs through
 - a set of innovative applications in different domains,
 - the use of public and private open geospatial data.





Approach

European NEtwork for Redistributing Geospatial Information to user Communities - Open Data

Already exists

- Applications: participative noise map
- Using smartphones (i.e. citizens) for a massive acquisition of noise data in urban environment
- Some existing apps: NoiseTube, WideNoise, NoiseSpy, ...

Our contribution

- Build a "qualified" noise database,
- Produce "added value" noise maps (with agregated indicators, ...),
- Open the database to the community.






- A "global infrastructure" made by specialists in Geomatics and in Acoustics.
- Development of specific treatments to qualify the noise.
- Use the database to build noise maps and indicators (with mixed data from participative measurements, laboratory measurements and simulations).





OnoM@p: System components and standards









ENERG Noise Capture

European NEtwork for Redistributing Geospatial Information to user Communities - Open Data



MEASUREMENT

- Instantaneous data dB(A)
- Global sound level
- Third octave band spectrum
- Min, Max and Mean values




RESULTS

- Equivalent SPL dB(A) (1s)
- Sound Exposure Level (SEL)
- Repartition of Noise Exposition (RNE)
- Noise spectrum
- Noise indicators: L , L L , L and L A10 A50 A90 AMin AMax



MAP

- Noise maps: geo-referenced SEL along the path (every 1s)
- Show:
 - last measurement
 - user's measurements
 - all users' measurements
- Internet access of the data with many information



ADDITIONAL CONTENTS

- About: project information
- Help: how to use the application
- History : manage data in the webphone
- Settings: manage user parameters







Web services

European NEtwork for Redistributing Geospatial Information to user Communities - Open Data

NoiseCapture




Virtual HUB







OnoMOP: Operating mode








Data issues

- Acquisition (quality of the sound measurement, accuracy of the GPS position, user practices).
- Data storage (time dimension, spatial relations).
- Data processing (availability, scale, statistical representativeness...).
- Visual display (map, dataviz...).





Quality control







Sound indicators

European NEtwork for Redistributing Geospatial Information to user Communities - Open Data

LAeq: equivalent noise level in dB(A), on the whole measurement duration. It is a standard environmental noise indicator, used for the evaluation of noise annoyance.

LA50: A-weighted noise level that is exceeded for 50% of the measurement period. LA50 is the median sound level

The A-weighting account for the relative loudness perceived by the human ear.










Ready to test?









Thanks for your attention

Questions?

Want to reuse data? There will be a contest:

- Contest is open to everyone. Contestants can form teams of max 4 people.
- Contestants submit a short business model and application mockup no more than 20 person hours of work.
- Contest opens in December 2016.
- Prizes are cash (1,500 for the 1st place, 1,000 for the 2nd, and 500 for the 3rd) and half-a-day consultation with ENERGIC-OD technology and business experts.
- For more information, visit ENERGIC-OD forums (http://www.energic-od.eu/).

