

# Efficient Temporal Kernels between Feature Sets for Time Series Classification

## *Supplementary material*

Romain Tavenard<sup>1</sup>, Simon Malinowski<sup>2</sup>, Laetitia Chapel<sup>3</sup>, Adeline Bailly<sup>1</sup>,  
Heider Sanchez<sup>4</sup>, and Benjamin Bustos<sup>4</sup>

<sup>1</sup> Univ. Rennes 2 / LETG-Rennes COSTEL, IRISA

<sup>2</sup> Univ. Rennes 1 / IRISA

<sup>3</sup> Univ. Bretagne Sud / IRISA

<sup>4</sup> Dept. of Computer Science, Univ. Chile

## 1 Full results table

The performance in terms of classification error rate of the proposed method ( $K_{FS}$ ) is given in Table 1, together with competing methods.

Dataset	BOSS [5]	DTD <sub>C</sub> [3]	LS [4]	TSBF[2]	BoW[1]	$K_{FS}$
Adiac *	0.235	0.299	0.478	0.230	0.248	<b>0.179</b>
ArrowHead *	0.166	0.280	<b>0.154</b>	0.246	0.194	0.246
Beef *	0.200	0.333	<b>0.133</b>	0.433	0.267	0.200
BeetleFly	0.100	0.350	0.200	0.200	0.100	<b>0.000</b>
BirdChicken	<b>0.050</b>	0.200	0.200	0.100	0.200	0.200
CBF *	0.002	0.020	0.009	0.012	<b>0.000</b>	<b>0.000</b>
Car *	0.167	0.217	0.233	0.217	0.083	<b>0.067</b>
ChlorineConcentration *	0.339	0.287	0.408	0.308	0.442	<b>0.135</b>
CinCECGtorso	0.113	0.148	0.130	0.288	0.180	<b>0.013</b>
Coffee *	<b>0.000</b>	<b>0.000</b>	<b>0.000</b>	<b>0.000</b>	<b>0.000</b>	<b>0.000</b>
Computers	<b>0.244</b>	0.284	0.416	<b>0.244</b>	0.328	0.296
CricketX	0.264	0.246	0.259	0.295	0.236	<b>0.233</b>
CricketY	0.246	<b>0.226</b>	0.282	0.264	<b>0.226</b>	0.236
CricketZ	0.254	0.226	0.259	0.285	<b>0.203</b>	0.215
DiatomSizeReduction *	0.069	0.085	<b>0.020</b>	0.101	0.111	0.046
Distal[...]AgeGroup *	0.252	0.338	0.281	0.288	<b>0.147</b>	0.175
Distal[...]Correct *	0.272	0.275	0.221	0.217	<b>0.178</b>	0.180
DistalPhalanxTW	0.324	0.424	0.374	0.324	<b>0.210</b>	0.215
ECG200 *	0.130	0.160	0.120	0.160	<b>0.100</b>	<b>0.100</b>
ECG5000 *	0.059	0.076	0.068	0.060	<b>0.051</b>	0.060
ECGFiveDays *	<b>0.000</b>	0.178	<b>0.000</b>	0.123	<b>0.000</b>	0.055
Earthquakes *	0.252	0.295	0.259	0.252	0.202	<b>0.199</b>
ElectricDevices *	<b>0.201</b>	0.406	0.413	0.297	0.361	0.340
FaceAll *	0.218	<b>0.101</b>	0.251	0.256	0.226	0.198
FaceFour *	<b>0.000</b>	0.182	0.034	<b>0.000</b>	0.023	0.045
FacesUCR *	<b>0.043</b>	0.092	0.061	0.133	0.054	0.075

FiftyWords	0.295	0.246	0.270	0.242	0.266	<b>0.198</b>
Fish	<b>0.011</b>	0.074	0.040	0.166	0.023	0.023
FordA	0.070	0.235	<b>0.043</b>	0.150	0.085	0.070
FordB	0.289	0.347	0.083	0.401	0.111	<b>0.082</b>
GunPoint	<b>0.000</b>	0.013	<b>0.000</b>	0.013	0.020	0.020
Ham *	0.333	0.448	0.333	<b>0.238</b>	0.352	0.276
HandOutlines *	<b>0.097</b>	0.135	0.519	0.146	0.137	0.119
Haptics *	0.539	0.601	0.532	0.510	<b>0.490</b>	0.506
Herring *	0.453	0.453	0.375	<b>0.359</b>	0.438	0.391
InlineSkate *	<b>0.484</b>	0.491	0.562	0.615	0.591	0.629
InsectWingbeatSound *	0.477	0.527	0.394	0.375	0.426	<b>0.372</b>
ItalyPowerDemand *	0.091	0.049	<b>0.040</b>	0.117	0.056	0.050
LargeKitchenAppliances	0.235	0.205	0.299	0.472	0.163	<b>0.136</b>
Lightning2 *	0.164	<b>0.131</b>	0.180	0.262	0.164	0.246
Lightning7	0.315	0.342	<b>0.205</b>	0.274	0.288	0.260
Mallat	0.062	0.073	0.050	<b>0.040</b>	0.146	0.068
Meat *	0.100	<b>0.067</b>	0.267	<b>0.067</b>	0.117	0.100
MedicalImages *	0.282	0.255	0.336	0.295	0.253	<b>0.246</b>
Middle[...]AgeGroup *	0.455	0.500	0.429	0.422	<b>0.200</b>	0.215
Middle[...]Correct *	0.220	0.258	0.220	<b>0.186</b>	0.312	0.318
MiddlePhalanxTW *	0.455	0.500	0.494	0.403	0.386	<b>0.358</b>
MoteStrain	0.121	0.232	0.117	<b>0.097</b>	0.169	0.179
NonInvasiveFatalECGThorax1	0.162	0.159	0.741	0.158	0.076	<b>0.045</b>
NonInvasiveFatalECGThorax2	0.099	0.110	0.230	0.138	0.061	<b>0.042</b>
OSULeaf	<b>0.045</b>	0.116	0.223	0.240	0.087	0.145
OliveOil *	<b>0.133</b>	<b>0.133</b>	0.833	0.167	0.167	<b>0.133</b>
PhalangesOutlinesCorrect *	0.228	0.239	0.235	<b>0.170</b>	0.219	0.179
Phoneme *	0.735	0.732	0.782	<b>0.724</b>	0.731	0.752
Plane	<b>0.000</b>	<b>0.000</b>	<b>0.000</b>	<b>0.000</b>	<b>0.000</b>	<b>0.000</b>
Proximal[...]AgeGroup *	0.166	0.205	0.166	0.151	<b>0.132</b>	0.180
Proximal[...]Correct *	0.151	0.206	0.151	<b>0.127</b>	0.192	0.131
ProximalPhalanxTW *	0.200	0.229	0.224	<b>0.190</b>	0.210	0.205
RefrigerationDevices	0.501	0.555	<b>0.485</b>	0.528	0.523	<b>0.485</b>
ScreenType *	0.536	0.563	0.571	<b>0.491</b>	0.525	0.523
ShapeletSim *	<b>0.000</b>	0.400	0.050	0.039	0.011	0.161
ShapesAll *	<b>0.092</b>	0.162	0.232	0.815	<b>0.092</b>	0.142
SmallKitchenAppliances *	0.275	0.352	0.336	0.328	0.285	<b>0.171</b>
SonyAIBORobotSurface1	0.368	0.290	0.190	0.205	<b>0.092</b>	0.218
SonyAIBORobotSurface2	0.141	<b>0.108</b>	0.125	0.222	0.179	0.153
StarlightCurves	0.022	0.038	0.053	0.023	<b>0.021</b>	0.022
Strawberry *	<b>0.024</b>	0.043	0.089	0.046	0.047	0.044
SwedishLeaf *	0.078	0.104	0.093	0.085	0.082	<b>0.061</b>
Symbols *	0.033	0.037	0.068	0.054	<b>0.017</b>	0.109
SyntheticControl	0.033	<b>0.003</b>	<b>0.003</b>	0.007	<b>0.003</b>	0.007
ToeSegmentation1	0.061	0.193	0.066	0.219	<b>0.026</b>	0.044
ToeSegmentation2	<b>0.038</b>	0.285	0.085	0.200	0.077	0.092
Trace	<b>0.000</b>	0.010	<b>0.000</b>	0.020	<b>0.000</b>	<b>0.000</b>

TwoLeadECG	0.019	0.015	<b>0.004</b>	0.134	0.024	0.040
TwoPatterns	0.007	<b>0.000</b>	0.007	0.024	0.007	<b>0.000</b>
UWaveGestureLibraryAll *	0.061	0.062	0.047	0.074	0.173	<b>0.029</b>
UWaveGestureLibraryX	0.238	0.225	0.209	<b>0.169</b>	0.231	0.171
UWaveGestureLibraryY	0.315	0.302	0.297	0.264	0.312	<b>0.246</b>
UWaveGestureLibraryZ	0.305	0.321	0.253	<b>0.228</b>	0.274	0.236
Wafer	0.005	0.007	<b>0.004</b>	0.005	0.008	0.005
Wine *	<b>0.259</b>	0.389	0.500	0.389	0.370	0.352
WordSynonyms *	0.362	<b>0.270</b>	0.393	0.312	0.365	0.281
Worms	0.442	0.351	0.390	0.312	0.343	<b>0.304</b>
WormsTwoClass	<b>0.169</b>	0.377	0.273	0.247	0.271	0.265
Yoga	0.082	0.144	0.166	0.181	0.131	<b>0.077</b>
Average rank	3.165	4.371	3.912	3.753	3.176	<b>2.624</b>

Table 1: Comparison of error rates between our temporal feature set kernel ( $D = 8192$ ) and local feature based state-of-the-art methods. Recall that BoW baseline operates on the exact same feature sets as our  $K_{FS}$ . Stars indicate datasets for which cross-validation leads to take temporal information into account ( $\gamma_t > 0$ ).

## 2 Parameter ranges

Table 2 gives the search range of the different parameters used for cross-validation.

Parameter name	Kernels	Parameter range
$C$	All kernels	$10^0 - 10^6$
$\gamma_K$	All kernels	$10^{-1} - 10^5$
$\gamma_f$	All variants of $K_{FS}$	$10^0 - 10^6$
$\gamma_t$	All temporal variants of $K_{FS}$	$10^0 - 10^6$

Table 2: Parameter grids for all kernels used in the paper. For all parameters, 5 values are selected at regular logscale locations in the range.

## 3 Timing experiments on more datasets

Fig. 1 represents the mean square error approximation of the approximated kernel matrix versus the timing for two datasets: *Adiac* and *Ham*. These datasets have been chosen so as to complement conclusions drawn in the paper for *ECG200* dataset. Indeed, *Ham* corresponds to a long time series case while *Adiac* has more training time series than *ECG200*. This figure matches Figure 2 of the paper and confirms that a good trade-off is obtained by the Fourier approximation.

Fig. 2 shows the error rate versus the feature map dimension for *Adiac* and *Ham* datasets. It confirms the statements made in the paper (Figure 4) about

the benefits of taking temporal information into account and of the kernel normalization.

Fig. 3 depicts the training and testing time of BoW, SQFD- $k$ -means and SQFD-Fourier as a function of the size of the training set for the same datasets. This figure matches Figure 3 of the paper, and identical conclusions can be drawn. The Fourier approximation leads to lower execution times than  $k$ -means approximation. Compared to BOW, training time is reduced, especially for large training sets.




Fig. 1: Mean Squared Error (MSE) *vs* timings of the approximated kernel matrix (*Adiac* and *Ham*).




Fig. 2: Error rates as a function of the feature map dimension (*Adiac* and *Ham*).




Fig. 3: Training and testing times as a function of the amount of training data (*Adiac* and *Ham*).

## 4 Pairwise comparisons

Figure 4 compares the performance of the proposed approach with two competing approaches : 1-nearest-neighbour (1NN) combined with DTW and BOSS-VS [6]. Classification error rates on the 85 datasets of the UCR-UEA repository are depicted, together with the Win/Tie/Lose scores and the  $p$ -values corresponding to one-sided Wilcoxon signed rank tests.

## References

1. Bailly, A., Malinowski, S., Tavenard, R., Chapel, L., Guyet, T.: Dense Bag-of-Temporal-SIFT-Words for Time Series Classification. Lecture Notes in Artificial Intelligence 9785, 17–30 (2016)




Fig. 4: Pairwise performance comparisons.

2. Baydogan, M.G., Runger, G., Tuv, E.: A Bag-of-Features Framework to Classify Time Series. *IEEE Transactions on Pattern Analysis and Machine Intelligence* 35(11), 2796–2802 (2013)
  3. Górecki, T., Luczak, M.: Non-isometric transforms in time series classification using DTW. *Knowledge-Based Systems* 61, 98–108 (2014)
  4. Grabocka, J., Schilling, N., Wistuba, M., Schmidt-Thieme, L.: Learning time-series shapelets. In: *Proceedings of the ACM SIGKDD International Conference on Knowledge Discovery and Data Mining*. pp. 392–401 (2014)
  5. Schäfer, P.: The BOSS is concerned with time series classification in the presence of noise. *Data Mining and Knowledge Discovery* 29(6), 1505–1530 (2014)
  6. Schäfer, P.: Scalable time series classification. *Data Mining and Knowledge Discovery* pp. 1–26 (2015)